

**Safety Data Sheet (SDS)**

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/22/2017

Reviewed on 03/22/2017

**\* 1 Identification**

- **Product Identifier**
- **Trade name: Precision Calibration Gas Mixture**
- **Product Number:**  
G-6115  
Martek Part Number: FCG33025, FCG33020, FCG33000, FCG50526, FCG50694
- **Relevant identified uses of the substance or mixture and uses advised against:**  
Used for calibration of gas measuring devices. Not suitable for human consumption.
- **Product Description** Calibration gas mixture consisting of Ethanol and Nitrogen.
- **Details of the Supplier of the Safety Data Sheet:**
- **Manufacturer/Supplier:**  
Martek Marine Ltd.  
Adwick Park, Rotherham, S63 5AB, UK  
Phone: +44 (0) 1709 599 222  
Fax: +44 (0) 1709 871 873  
Web: www.martek-marine.com  
Email: info@martek-marine.com
- **Emergency telephone number:**  
Inside the US: 1-800-424-9300 (CHEMTREC, 24 hours)  
Outside the US: 1-703-527-3887 (CHEMTREC, 24 hours)

**2 Hazard(s) Identification**

- **Classification of the substance or mixture:**



GHS04 Gas cylinder

Press. Gas                      H280 Contains gas under pressure; may explode if heated.

Simple Asphyxiant                      May displace oxygen and cause rapid suffocation.

- **Label elements:**
- **GHS label elements**  
The substance is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms:**



GHS04

- **Signal word:** Warning
- **Hazard statements:**  
H280 Contains gas under pressure; may explode if heated.  
May displace oxygen and cause rapid suffocation.
- **Precautionary statements:**  
P410+P403 Protect from sunlight. Store in a well-ventilated place.
- **Unknown acute toxicity:**  
100 % of the mixture consists of component(s) of unknown toxicity.

(Contd. on page 2)

# Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/22/2017

Reviewed on 03/22/2017

**Trade name: Precision Calibration Gas Mixture**

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



The substance possesses oxidizing properties.

- **HMS-ratings (scale 0 - 4)**



- **Hazard(s) not otherwise classified (HNOC):** None known

## 3 Composition/Information on Ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of substances listed below with non-hazardous additions.

### · **Dangerous Components:**

CAS: 7727-37-9	Nitrogen	99.96 - 99.9922%
RTECS: QW 9700000	⚠ Press. Gas, H280; Simple Asphyxiant	
CAS: 64-17-5	Ethanol	0.0078 - 0.04%
RTECS: KQ 6300000	⚠ Flam. Liq. 2, H225; ⚠ Carc. 1A, H350; ⚠ Skin Irrit. 2, H315; STOT SE 3, H335; Eye Irrit. 2B, H320	

## 4 First-Aid Measures

- **Description of first aid measures:**
- **After inhalation:**  
Generally the product does not irritate with inhalation.  
Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**  
Generally the product does not irritate the skin.  
In cases of contact with liquified material, frostbite may occur. Immerse frostbite in cool-warm water and seek medical attention.  
Wash with soap and water.  
If skin irritation occurs, consult a doctor.
- **After eye contact:**  
Not anticipated under normal use.  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:**  
Not a normal route of entry.  
If swallowed and symptoms occur, consult a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed:** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed:**  
No further relevant information available.

(Contd. on page 3)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/22/2017

Reviewed on 03/22/2017

**Trade name: Precision Calibration Gas Mixture**

### 5 Fire-Fighting Measures

- **Extinguishing media:**
- **Suitable extinguishing agents:**  
Use fire fighting measures that suit the environment.  
Use water spray to cool fire-exposed containers.
- **Special hazards arising from the substance or mixture:**  
Closed containers may explode when exposed to extreme heat.  
If incinerated, product will release the following toxic fumes: Oxides of Carbon and Nitrogen (NOx).
- **Advice for firefighters:**  
This gas mixture is not flammable; however, containers, when involved in fire, may rupture or burst in the heat of the fire.
- **Protective equipment:**  
As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

### 6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures:**  
In a confined area, NIOSH approved respiratory protection may be required.  
Treat any fumes as toxic.  
Wear protective equipment. Keep unprotected persons away.  
Ensure adequate ventilation.
- **Environmental precautions:** Inform authorities in case of gas release.
- **Methods and material for containment and cleaning up:**  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.  
Dispose of the collected material according to regulations.
- **Reference to other sections:**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### 7 Handling and Storage

- **Handling**
- **Precautions for safe handling:**  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.  
Be aware of any signs of dizziness or fatigue; exposures to fatal concentrations of this gas mixture could occur without any significant warning symptoms due to the potential for oxygen deficiency (simple asphyxiation). Do not attempt to adjust, repair or in any other way modify the cylinders containing this gas mixture. If there is a malfunction or another type of operational problem, contact nearest distributor immediately.
- **Information about protection against explosions and fires:**  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.  
Keep protective respiratory device available.  
Do not cut, grind or weld on container that contains or contained product.  
Do not spray on a naked flame or any incandescent material.
- **Conditions for safe storage, including any incompatibilities:** Store away from strong oxidizing agents.

(Contd. on page 4)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/22/2017

Reviewed on 03/22/2017

**Trade name: Precision Calibration Gas Mixture**

- **Storage**

- **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Cylinders should be firmly secured to prevent falling or being knocked over. Cylinders must be protected from the environment, and preferably kept at room temperature. Cylinders should be stored in dry, well-ventilated areas, away from sources of heat, ignition, and direct sunlight. Protect cylinders against physical damage. Full and empty cylinders should be segregated. Use a "first-on, first-out" inventory system to prevent full containers from being stored for long periods of time.

- **Information about storage in one common storage facility:** Not required.

- **Further information about storage conditions:** Store in cool, dry conditions in well sealed receptacles.

- **Specific end use(s):** No further relevant information available.

### 8 Exposure Controls/Personal Protection

- **Additional information about design of technical systems:** No further data; see section 7.

- **Control parameters:**

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94). Use mechanical (general) ventilation for storage areas. Use appropriate ventilation as required to keep Exposure Limits in Air below TLV & PEL limits.

- **Components with occupational exposure limits:**

**7727-37-9 Nitrogen**

TLV withdrawn TLV, see App. F; simple asphyxiant

**64-17-5 Ethanol**

PEL Long-term value: 1900 mg/m<sup>3</sup>, 1000 ppm

REL Long-term value: 1900 mg/m<sup>3</sup>, 1000 ppm

TLV Short-term value: 1880 mg/m<sup>3</sup>, 1000 ppm  
Upper Respiratory Tract irritation

- **Additional information:** The lists that were valid during the creation of this SDS were used as basis.

- **Exposure controls:**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

- **Breathing equipment:**

Not necessary if room is well-ventilated.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure, use respiratory protective device that is independent of circulating air.

- **Protection of hands:** Not required.

- **Eye protection:** Not necessary under normal conditions.

### 9 Physical and Chemical Properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

**Form:**

Gaseous

**Color:**

Clear, colorless

- **Odor:**

Odorless

- **Odor threshold:**

Not determined.

- **pH-value:**

Not determined.

(Contd. on page 5)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/22/2017

Reviewed on 03/22/2017

**Trade name: Precision Calibration Gas Mixture**

- **Change in condition**
  - Melting point/Melting range:** Not determined.
  - Boiling point/Boiling range:** Not determined.
- **Flash point:** None
- **Flammability (solid, gaseous):** Product is not flammable.
- **Ignition temperature:**
  - Decomposition temperature:** Not determined.
- **Auto igniting:** Product is not self-igniting.
- **Danger of explosion:** Not determined.
- **Explosion limits:**
  - Lower:** Not determined.
  - Upper:** Not determined.
- **Vapor pressure:** Not determined.
- **Density:**
  - Relative density:** Not determined.
  - Vapor density:** Not determined.
  - Evaporation rate:** Not applicable.
- **Solubility in / Miscibility with:**
  - Water:** Not miscible or difficult to mix.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
  - Dynamic:** Not determined.
  - Kinematic:** Not determined.
- **Solvent content:**
  - Organic solvents:** 0.0 %
- **Other information:** No further relevant information available.

### 10 Stability and Reactivity

- **Reactivity:** No further relevant information available.
- **Chemical stability:** Stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions:** No dangerous reactions known.
- **Conditions to avoid:** No further relevant information available.
- **Incompatible materials:** Strong oxidizing agents.
- **Hazardous decomposition products:** Carbon Oxides and Nitrogen Oxides (NOx).

(Contd. on page 6)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/22/2017

Reviewed on 03/22/2017

Trade name: Precision Calibration Gas Mixture

### 11 Toxicological Information

- **Information on toxicological effects:**

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

#### 64-17-5 Ethanol

Oral	LD50	7060 mg/kg (Rat) Remarks: Lungs, Thorax, or Respiration: Other changes. Carcinogenicity - Mouse - Oral Tumorigenic: Equivocal tumorigenic agent by RTECS criteria. Liver: Tumors. Blood: Lymphomas including Hodgkin's disease. Central nervous system depression, narcosis, Damage to the heart., To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated. Heart - Irregularities - Based on Human Evidence Central nervous system - Breathing difficulties - Based on Human Evidence Stomach - Irregularities - Based on Human Evidence
Inhalative	LC50/4 h	20000 mg/l (Rat)
	LC50/96 hours	12900-15300 mg/l (Trout)

- **Primary irritant effect:**

- **On the skin:** No irritating effect.

- **On the eye:** No irritating effect.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

- **Carcinogenic categories:**

- **IARC (International Agency for Research on Cancer):**

- Group 1 - Carcinogenic to humans
- Group 2A - Probably carcinogenic to humans
- Group 2B - Possibly carcinogenic to humans
- Group 3 - Not classifiable as to its carcinogenicity to humans
- Group 4 - Probably not carcinogenic to humans

None of the ingredients are listed.

- **NTP (National Toxicology Program):**

None of the ingredients are listed.

- **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

### 12 Ecological Information

- **Toxicity:**

- **Aquatic toxicity:**

#### 64-17-5 Ethanol

EC50 34900 mg/l (Daphnia)

- **Persistence and degradability:** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential:** No further relevant information available.

- **Mobility in soil:** No further relevant information available.

(Contd. on page 7)

# Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/22/2017

Reviewed on 03/22/2017

**Trade name: Precision Calibration Gas Mixture**

- **Additional ecological information:**
- **General notes:** Generally not hazardous for water.
- **Results of PBT and vPvB assessment:**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects:** No further relevant information available.

## 13 Disposal Considerations

- **Waste treatment methods:**
- **Recommendation:**  
Release all residual gas pressure in a well ventilated area. Verify the cylinder is completely empty (0 PSIG). Remove or cover any hazard labels. Return empty cylinder for recycling.  
NOTE: Check with the local waste authority before placing any gas cylinder into waste container for pickup.
- **Waste disposal key:**  
The U.S. EPA has not published waste disposal numbers for this product's components.
- **Uncleaned packagings**
- **Recommendation:** Return cylinder and unused product to supplier.

## 14 Transport Information

- **UN-Number:**
- **DOT, ADR/ADN, IMDG, IATA** UN1956
- **UN proper shipping name:**
- **DOT** Compressed gas, n.o.s. (Nitrogen, Ethanol)
- **ADR/ADN** UN1956 Compressed gas, n.o.s. (Nitrogen, Ethanol)
- **IMDG, IATA** COMPRESSED GAS, N.O.S. (NITROGEN, ETHANOL)
- **Transport hazard class(es):**
- **DOT**



- **Class:** 2.2
- **Label:** 2.2

### · ADR/ADN



- **Class:** 2.2 1A
- **Label:** 2.2

### · IMDG, IATA



- **Class:** 2.2
- **Label:** 2.2

(Contd. on page 8)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/22/2017

Reviewed on 03/22/2017

**Trade name: Precision Calibration Gas Mixture**

- |   |   |
|---|---|
| · <b>Packing group:</b>   | Non-Regulated Material  |
| · <b>DOT, ADR/ADN, IMDG, IATA</b>   | Not applicable.   |
| · <b>Environmental hazards:</b>   | Not applicable.   |
| · <b>Special precautions for user:</b>  | Not applicable.   |
| · <b>Danger code (Kemler):</b>  | 20  |
| · <b>EMS Number:</b>  | F-C,S-V   |
| · <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:</b> | Not applicable.   |
| · <b>Transport/Additional information:</b>  |   |
| · <b>DOT</b>  |   |
| · <b>Quantity limitations:</b>  | On passenger aircraft/rail: 75 kg<br>On cargo aircraft only: 150 kg |
- 
- |                                    |  |
|------------------------------------|--|
| · <b>ADR/ADN</b>                   |  |
| · <b>Excepted quantities (EQ):</b> | Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 1000 ml |
- 
- |                                    |  |
|------------------------------------|--|
| · <b>IMDG</b>                      |  |
| · <b>Limited quantities (LQ):</b>  | 120 ml   |
| · <b>Excepted quantities (EQ):</b> | Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 1000 ml |
| · <b>UN "Model Regulation":</b>    | UN1956, Compressed gas, n.o.s. (Nitrogen, Ethanol), 2.2  |

### 15 Regulatory Information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture:**
- **SARA (Superfund Amendments and Reauthorization):**

· <b>Section 355 (extremely hazardous substances):</b>
--

None of the ingredients are listed.
-------------------------------------

· <b>Section 313 (Specific toxic chemical listings):</b>
--

None of the ingredients are listed.
-------------------------------------

· <b>TSCA (Toxic Substances Control Act):</b>
---

All ingredients are listed or exempt from listing.
--

· <b>California Proposition 65:</b>
-------------------------------------

· <b>Chemicals known to cause cancer:</b>
---

None of the ingredients are listed.
-------------------------------------

· <b>Chemicals known to cause reproductive toxicity for females:</b>
--

None of the ingredients are listed.
-------------------------------------

· <b>Chemicals known to cause reproductive toxicity for males:</b>
--

None of the ingredients are listed.
-------------------------------------

· <b>Chemicals known to cause developmental toxicity:</b>
---

None of the ingredients are listed.
-------------------------------------

· <b>Carcinogenic categories:</b>
-----------------------------------

· <b>EPA (Environmental Protection Agency):</b>
---

None of the ingredients are listed.
-------------------------------------

(Contd. on page 9)




## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/22/2017

Reviewed on 03/22/2017

**Trade name: Precision Calibration Gas Mixture**

· <b>TLV (Threshold Limit Value established by ACGIH):</b>		
64-17-5	Ethanol	A3
· <b>NIOSH-Ca (National Institute for Occupational Safety and Health):</b>		
None of the ingredients are listed.		
· <b>GHS label elements</b>		
The substance is classified and labeled according to the Globally Harmonized System (GHS).		
· <b>Hazard pictograms:</b>		
		
GHS04		
· <b>Signal word:</b> Warning		
· <b>Hazard statements:</b>		
H280 Contains gas under pressure; may explode if heated.		
May displace oxygen and cause rapid suffocation.		
· <b>Precautionary statements:</b>		
P410+P403 Protect from sunlight. Store in a well-ventilated place.		
· <b>National regulations:</b>		
The product is subject to be classified according with the latest version of the regulations on hazardous substances.		
· <b>Chemical safety assessment:</b> A Chemical Safety Assessment has not been carried out.		

### 16 Other Information

· **Relevant phrases:**

Martek Marine Ltd., makes no express or implied warranties, guarantees or representations regarding the product or the information herein, including but not limited to any implied warranty or merchantability or fitness for use. Martek Marine Ltd. shall not be liable for any personal injury, property or other damages of any nature, whether compensatory, consequential, exemplary, or otherwise, resulting from any publication, use or reliance upon the information herein.

· **Date of preparation / last revision:** 03/22/2017 / -

· **Abbreviations and acronyms:**

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road  
 ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
 IMDG: International Maritime Code for Dangerous Goods  
 DOT: US Department of Transportation  
 IATA: International Air Transport Association  
 ACGIH: American Conference of Governmental Industrial Hygienists  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 NFPA: National Fire Protection Association (USA)  
 HMIS: Hazardous Materials Identification System (USA)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 NIOSH: National Institute for Occupational Safety and Health  
 OSHA: Occupational Safety & Health Administration  
 TLV: Threshold Limit Value  
 PEL: Permissible Exposure Limit  
 REL: Recommended Exposure Limit  
 Press. Gas: Gases under pressure – Compressed gas  
 Press. Gas: Gases under pressure – Dissolved gas

(Contd. on page 10)

## **Safety Data Sheet (SDS)**

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/22/2017

Reviewed on 03/22/2017

**Trade name: Precision Calibration Gas Mixture**

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2B: Serious eye damage/eye irritation – Category 2B

Carc. 1A: Carcinogenicity – Category 1A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· **\* Data compared to the previous version altered.**

SDS created by MSDS Authoring Services    [www.msdsauthoring.com](http://www.msdsauthoring.com)    +1-877-204-9106